

MOTOR OIL FOR PASSENDER CARS

 Technical Data Sheet (TDS)
AZOVMAST 5W30 SN/CF
**FULLY SYNTHETIC HIGH-TECH MOTOR OIL**

Produced of high-quality synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life.

Provides improved safety as compared to mineral and semi-synthetic oils.

Special low-ash formula



Temperature range :-30...+40 °C

Compliance to international standards

SAE 5W-30

API SN/CF

ACEA A3/B3/B4

VW 502.0/505.00/505.01

MB 229.3

BMW LL-01

Opel GM-LL-025

Application area Intended for **modern gasoline and diesel engines of passenger cars and vans**. Compatible with injector and multivalve engines, including turbocharged, with intercooler and catalyst.

Properties/Benefits

Reliable engine protection under various conditions

Optimum for the use both in urban cycle and cross-country conditions

Reduces fuel consumption

Significantly extends engine service life

Provides safe engine start at low temperatures in winter

Characteristic	Value
K. viscosity @ 100°C, mm ² /s	11.9
Density @ 20°C, kg/m ³	870
Viscosity index	150
TBN, mg KOH/g	9.75
Flash point COC, °C	210
Pour point, °C	-35

Enable packing

