

## MOTOR OIL FOR PASSENDER CARS

**Technical Data Sheet (TDS)**  
**5W40 SYNTHETIC**
**SYNTHETIC HIGH-TECH MOTOR OIL**

Produced of high-quality foreign synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life

Provides increased safety level as compared to mineral and semi-synthetic oils. Special low-ash formula. Has an extended drain interval



Temperature range :-30...+45 °C

**Compliance to international standards****SAE 5W-40**

MB 229.3 BMW LL-01

**API SN/CF**

Opel GM-LL-025

**ACEA A3/B3/B4**

VW 502.0/505.00

**Application area**

Intended for modern gasoline and diesel engines of passenger cars and vans. Compatible with injector and multivalve engines, including turbocharged, with intercooler and catalyst.

**Properties/ Benefits**

- Reliable engine protection under various conditions incl. extreme operating mode;
- Reduces fuel consumption;
- Extends engine service life
- Excellent low temperature, antifriction, anticorrosion, detergent and antioxidizing properties;
- Provides safe engine start at low temperatures in winter

Characteristic	Value
K. viscosity @ 100°C, mm <sup>2</sup> /s	14,3
Density @ 20°C, kg/m <sup>3</sup>	860
Viscosity index	180
TBN, mg KOH/g	8,3
Flash point COC, °C	216
Pour point, °C	-35
<b>Enable packing</b>	